

Everwipe™ Series

Product Typical Properties

STYLE: 606 Series

DESCRIPTION: Spunlaced Nonwoven – 2.0 oz/yd² –
 55% Woodpulp/45% Polyester, White

DATE: February 26, 2008

Property	Units	Value ¹	Range ¹	Test Method
Basis Weight	oz/yd ²	2.02	1.88 – 2.16	ASTM D3776
Thickness	mils	14.0	11.8 – 16.2	ASTM D1777
XD Dry Grab Tensile	lbs.	19.9	14.8 – 25.0	ASTM D5034
XD Elongation	%	76	-----	ASTM D5034
XD Wet Grab Tensile	lbs.	15.0	-----	ASTM D5034
XD Wet Elongation	%	97	-----	ASTM D5034
MD Dry Grab Tensile	lbs.	34.4	-----	ASTM D5034
MD Elongation	%	25.6	-----	ASTM D5034
MD Wet Grab Tensile	lbs.	24.2	-----	ASTM D5034
MD Wet Elongation	%	38.5	-----	ASTM D5034
Capacity	Ae	mL/m ²	292	INDA 10.2 (98)
	Ai	mL/g	4.3	
Rate	Re	mL/m ² /s	1840	INDA 10.2 (98)
	Ri	mL/g/s	27.1	

¹ This information is the best currently available for this product. It is subject to revision as additional knowledge is gained. Legacy Converting makes no guarantee of results and assumes no obligation or liability whatsoever in connection with this information. This publication is not a license to operate under, or intended to suggest infringement of, any existing patents.